

# SAFETY DATA SHEET

### Date of last issue: 04/08/2019 Supersedes: 11/18/2016

### **SECTION 1. IDENTIFICATION**

Product name	:	STAPLES® Hand Sanitizer
Product code	:	27456, 27458
Manufacturer or supplier's Company name of supplier		ails STAPLES CONTRACT & COMMERCIAL, INC.
Address	:	500 Staples Drive Framingham, MA 01702
Telephone	:	1-888-322-0912
Emergency telephone	:	1-888-322-0912

# Recommended use of the chemical and restrictions on use

Recommended use	:	Hand Sanitizer
Restrictions on use	:	This is a personal care or cosmetic product that is safe for consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer. While this material is not considered hazardous, this SDS contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions as well as unusual and unintended exposures such as large spills. This SDS should be retained and available for employees and other users of this product. For specific intended-use guidance, please refer to the information provided on the package or instruction sheet.

# **SECTION 2. HAZARDS IDENTIFICATION**

GHS Classification Flammable liquids	: Category 3
Eye irritation	: Category 2A
GHS Label element Hazard pictograms	
Signal Word	: Warning
Hazard Statements	: H226 Flammable liquid and vapor. H319 Causes serious eye irritation.

Precautionary Statements

: Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. -No smoking. P233 Keep container tightly closed. P241 Use explosion-proof electrical/ventilating/lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 Wear eye protection/ face protection. **Response:** P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/ attention. Storage: P403 + P235 Store in a well-ventilated place. Keep cool. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

Vapors may form explosive mixture with air.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### **Hazardous ingredients**

Chemical Name	CAS-No.	Concentration (%)
Ethanol	64-17-5	>= 50 - < 70
Propan-2-ol	67-63-0	>= 1 - < 5

#### **SECTION 4. FIRST AID MEASURES**

General advice	<ul> <li>In the case of accident or if you feel unwell, seek medical advice immediately.</li> <li>When symptoms persist or in all cases of doubt seek medical advice.</li> </ul>
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

	If easy to do, remove contact lens, if worn. Get medical attention.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: Causes serious eye irritation.
Protection of first-aiders	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
Notes to physician	: Treat symptomatically and supportively.

# SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO2)	
Unsuitable extinguishing media	:	High volume water jet	
Specific hazards during fire fighting	:	Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.	
Hazardous combustion prod- ucts	:	Carbon oxides	
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.	
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.	

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Remove all sources of ignition.
protective equipment and	Use personal protective equipment.
emergency procedures	Follow safe handling advice and personal protective
	equipment recommendations.

Environmental precautions	Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	<ul> <li>Non-sparking tools should be used.</li> <li>Soak up with inert absorbent material.</li> <li>Suppress (knock down) gases/vapors/mists with a water spray jet.</li> <li>For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.</li> <li>Clean up remaining materials from spill with suitable absorbent.</li> <li>Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.</li> <li>Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.</li> </ul>

# SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.
Advice on safe handling	:	Do not breathe vapors or spray mist. Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	:	Keep in properly labeled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Materials to avoid	<ul> <li>Do not store with the following product types: Strong oxidizing agents Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures which in contact with water emit flammable gases Explosives</li> </ul>
	Gases

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1

### **Biological occupational exposure limits**

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentratio n	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI

Engineering measures

: Minimize workplace exposure concentrations. Use only in an area equipped with explosion proof exhaust ventilation. Use with local exhaust ventilation.

# Personal protective equipment

Respiratory protection

: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are

			unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
Hand prot			
Materia	1	:	Impervious gloves
Materia	I	:	Flame retardant gloves
Remark	٢S	•	Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Eye prote	ction	:	Wear the following personal protective equipment: Safety goggles
Skin and I	oody protection	:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: Flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Hygiene n	neasures	:	Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Color : clear, Colorless to pale yellow
Odor : citrus
Odor Threshold : No data available
рН : 6.5 - 8.5
Melting point/freezing point : No data available

# SAFETY DATA SHEET

# **STAPLES®** Hand Sanitizer

Initial boiling point and boiling range	: 70 °C
Flash point	: 25 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Density	: 0.8750 g/cm3
Solubility(ies) Water solubility	: soluble
Partition coefficient: n- octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: The substance or mixture is not classified self-reactive.
Viscosity Viscosity, kinematic	: 3,500 - 23,000 mm2/s (20 °C)
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

# SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac- tions	<ul> <li>Flammable liquid and vapor.</li> <li>Vapors may form explosive mixture with air.</li> <li>Can react with strong oxidizing agents.</li> </ul>
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes Inhalation Skin contact Ingestion Eye contact	s of exposure
Acute toxicity Not classified based on avail	able information.
Product:	
Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Ingredients:	
Ethanol:	
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 124.7 mg/l Exposure time: 4 h Test atmosphere: vapor
Propan-2-ol:	
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 72.6 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rat): > 5,000 mg/kg

### Skin corrosion/irritation

Not classified based on available information.

Product:

Result: No skin irritation

# Ingredients:

**Ethanol:** Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

# Propan-2-ol:

Species: Rabbit Result: No skin irritation

# Serious eye damage/eye irritation

Causes serious eye irritation.

### Ingredients:

### Ethanol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days Method: OECD Test Guideline 405

# Propan-2-ol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

### Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

### Product:

Assessment: Does not cause skin sensitization.

### Ingredients:

#### Ethanol:

Test Type: Local lymph node assay (LLNA) Routes of exposure: Skin contact Species: Mouse Result: negative

### Propan-2-ol:

Test Type: Buehler Test Routes of exposure: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

### Germ cell mutagenicity

Not classified based on available information.

# Ingredients:

Ethanol: Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Ingestion Result: negative
<b>Propan-2-ol:</b> Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

### Carcinogenicity

Not classified based on available information.

# Ingredients:

Propan-2-ol: Species: Rat Application Route: inhalation (vapor) Exposure time: 104 weeks Method: OECD Test Guideline 451 **Result:** negative

# IARC

IARC	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

# **Reproductive toxicity**

Not classified based on available information.

by NTP.

#### **Ingredients:** Ethanol

Ethanol:		
Effects on fertility	Test Type: Two-generation reproduction toxicity study Species: Mouse Application Route: Ingestion Method: OECD Test Guideline 416 Result: negative	
Propan-2-ol:		
Effects on fertility	<ul> <li>Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative</li> </ul>	
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative	

### STOT-single exposure

Not classified based on available information.

### Ingredients:

#### Propan-2-ol:

Assessment: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

# **STAPLES®** Hand Sanitizer

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

# Ingredients:

Ethanol: Species: Rat NOAEL: 2,400 mg/kg Application Route: Ingestion Exposure time: 2 y

#### Propan-2-ol:

Species: Rat NOAEL: 5000 ppm Application Route: inhalation (vapor) Exposure time: 104 w Method: OECD Test Guideline 413

#### Aspiration toxicity

Not classified based on available information.

### **SECTION 12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

Ingredients:		
Ethanol: Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d
Toxicity to bacteria	:	EC50 (Photobacterium phosphoreum): 32.1 mg/l Exposure time: 0.25 h
Propan-2-ol:		
•	:	LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to algae	:	ErC50 (Scenedesmus quadricauda (Green algae)): > 1,800

	mg/l Exposure time: 8 d
Toxicity to bacteria	: EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h
Persistence and degradabi	lity
Ingredients:	
Ethanol: Biodegradability	: Result: Readily biodegradable. Biodegradation: 84 % Exposure time: 20 d
<b>Propan-2-ol:</b> Biodegradability	: Result: rapidly degradable
Bioaccumulative potential	
Ingredients:	
Ethanol: Partition coefficient: n- octanol/water	: log Pow: -0.35
<b>Propan-2-ol:</b> Partition coefficient: n- octanol/water	: log Pow: 0.05
Mobility in soil	
No data available	
Other adverse effects	
No data available	

# SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: Dispose of in accordance with local regulations.
Contaminated packaging	<ul> <li>Dispose of as unused product.</li> <li>Empty containers should be taken to an approved waste handling site for recycling or disposal.</li> <li>Do not burn, or use a cutting torch on, the empty drum.</li> </ul>

# SECTION 14. TRANSPORT INFORMATION

# International Regulation

# UNRTDG

UN number

: UN 1987

Proper shipping name Class Packing group Labels	<ul> <li>ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol)</li> <li>3</li> <li>III</li> <li>3</li> </ul>
<b>IATA-DGR</b> UN/ID No. Proper shipping name	: UN 1987 : Alcohols, n.o.s. (Ethanol, Propan-2-ol)
Class	: 3
Packing group	: 111
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355
IMDG-Code	
UN number	: UN 1987
Proper shipping name	: ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol)
Class	: 3
Packing group	: !!!
Labels EmS Code	: 3 : F-E, S-D
Marine pollutant	. F-E, S-D : NO

# **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable for product as supplied.

### Domestic regulation

<b>49 CFR</b> UN/ID/NA number Proper shipping name	: UN 1987 : ALCOHOLS, N.O.S.
Class	: 3
Packing group	: III
Labels	: FLAMMABLE LIQUID
ERG Code	: 127
Marine pollutant	: no

# **SECTION 15. REGULATORY INFORMATION**

# EPCRA - Emergency Planning and Community Right-to-Know

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.


SARA 311/312 Hazards	s : Fire Hazard Acute Health Haza	ard			
SARA 302		his material are subject to th ARA Title III, Section 302.	he reporting		
SARA 313		The following components are subject to reporting levels established by SARA Title III, Section 313:			
	Propan-2-ol	67-63-0	3.4086 %		
US State Regulations					
Pennsylvania Right To	o Know				
Ethanc	bl	64-17-5	50 - 70 %		
Water		7732-18-5	30 - 50 %		
Propar	ו-2-ol	67-63-0	1 - 5 %		
New Jersey Right To Know					
Ethano	bl	64-17-5	50 - 70 %		
Water		7732-18-5	30 - 50 %		
Propar	ו-2-ol	67-63-0	1 - 5 %		
California Prop 65	State of California	This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.			
The ingredients of this product are reported in the following inventories:					
AICS	: All ingredients liste	-			

### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)

# **SECTION 16. OTHER INFORMATION**

### **Further information**



HMIS III:



0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average
Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/

#### **Prepared By:** Regulatory Specialist, Staples Brand Group, (508) 253-5000

Always follow label directions carefully when using this or any other chemical product. If information about this product is required, please contact Staples at 1-888-322-0912 or visit our website at www.staplesadvantage.com. Keep Safety Data Sheets filed and organized in an area accessible to workers according to all applicable regulations.

All information contained in this SDS is provided to the best of Staples Contract & Commercial Inc's knowledge. No warranty is made with respect to this information expressed or implied, including warranties of merchantability or fitness for a particular purpose. Users are responsible for verifying the information under their own operating conditions to determine whether the products listed in the SDS are suitable for their intended use. Users are responsible for compliance with all laws and regulations as may be required by their receipt of the information and use of the products provided with this SDS.

US / Z8